



# Planar PZN2710Q

## 27" Docking Monitor

The Planar® PZN2710Q is a 27" Quad HD USB Type - C Docking monitor with integrated docking station provides a simple and easy way to connect a PC/laptop to the monitor. The monitor enables a single USB Type C cable to deliver audio, video, data, network connectivity, daisy chain, and power delivery up to 65 watts. The Planar PZN2710Q suits nicely into education, home, office or healthcare applications.



SPECIFICATION	DETAIL
Product Name	PZN2710Q
Planar Part Number	998-2124-00
Viewable Size	27" diagonal (23.53" x 13.21")
Aspect Ratio	16:9
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	178° Horizontal and Vertical
Response Time (typ)	6 ms (GTG)
Brightness (Typical)	300 cd/m <sup>2</sup>
Display Type	IPS LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	2560 x 1440 WQHD
Tilt Range	-5° to +20°
Palette	16.7 million colors
Pixel Pitch	0.2331 mm
Refresh Rate	48-75Hz (60Hz recommended)
Dimensions (W x H x D)	24.2" x 20.5" x 9.1" (612.84 mm x 519.39 mm x 229.63 mm)

<b>Dimensions without Stand</b>	24.2" x 14.5" x 2.1" (612.84 mm x 367.46 mm x 52.3 mm)
<b>Panel Depth</b>	2.1" (52.3 mm)
<b>Display Weight</b>	13.6 lb/6.16 kg (9.2 lb/ 4.17 kg without stand)
<b>Shipping weight</b>	16.5 lb (7.5 kg)
<b>Video Inputs</b>	USB Type C (DisplayPort Alt Mode), DisplayPort, HDMI®
<b>Video Outputs</b>	DisplayPort
<b>HDCP</b>	Yes
<b>Audio Output</b>	Integrated 2W/channel stereo speakers, headphone jack
<b>External Connections</b>	USB Type C, HDMI 19-pin, DisplayPort 20-pin, 3.5mm headphone out, USB 3.2 Gen 1 (Type A) x 3, RJ45, DisplayPort 20-pin (out)
<b>USB</b>	USB-C x 1 (Upstream) (5Gbps), USB3.2 Gen1 x 3 (Downstream)
<b>USB C Power Delivery</b>	USB C (Up to 65W) (5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A)
<b>RJ45</b>	Ethernet LAN (10M/100M/1000M)
<b>Compatibility</b>	PC and Mac® (adapter may be required for Mac)
<b>Power Supply</b>	External (DC power)
<b>Power Consumption (max)</b>	35W typical (<0.5W standby)
<b>Power Requirements</b>	AC 100/240 VAC
<b>Operating Temperature</b>	0° to +40°C (32° to 104°F)
<b>Humidity</b>	10 - 85% RH (non-condensing)
<b>Mount</b>	Built-in 100 mm VESA, back
<b>Product Approvals</b>	cTUVus, CE , FCC-B, RoHS
<b>Recommended Usage</b>	Up to 16 hours per day
<b>Service and Support</b>	3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US.
<b>Options / Features</b>	IPS panel, Wide color consistent viewing angle, Discreet branding, Height adjustment: 4.3" (120cmm), Swivel range 60° (30° left, 30° right), Pivot 90°, Anti-glare coating ,Multi-language display, On screen display (OSD), Kensington® Security Slot

<b>Blue Light Reduction</b>	Yes
<b>Flicker Free</b>	Yes
<b>In the Box</b>	PZN2710Q 27" LCD Monitor, Power Cord, HDMI cable, DP Cable, USB Type-C Cable, User's Guide
<b>UPC</b>	8 10689 00803 3
<b>Recommended Daisy Chain Monitor</b>	PXN2710Q (998-2123-00)
<b>HDMI®</b>	Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 9/27/2024*

*© Copyright 2024 Planar Systems, Inc. All rights reserved*