



Planar PZN3210U

32" 4K Docking Monitor

The Planar® PZN3210U is a 32", 4K, USB Type-C Docking monitor. The integrated docking station provides a simple and easy way to connect a PC/laptop to the monitor. A single Type C cable provides audio, video, data, network connectivity via the gigabit Ethernet port, and power delivery up to 65 watts. The Planar PZN3210U is excellent for education, home, office or healthcare applications.



| SPECIFICATION | DETAIL |
|------------------------|---|
| Product Name | PZN3210U |
| Planar Part Number | 998-2549-00 |
| Viewable Size | 31.5" diagonal (27.45" x 15.44") |
| Aspect Ratio | 16:9 |
| Contrast Ratio (typ) | 1000:1 |
| Viewing Angle (typ) | 178° Horizontal and Vertical |
| Response Time (typ) | 5 ms (GTG) |
| Brightness (Typical) | 350 cd/m ² |
| Display Type | IPS LCD Active Matrix Flat Panel Display (TFT) |
| Display Resolution | 3840 x 2160 UHD |
| Tilt Range | -6° to +24° |
| Palette | 1.07 billion colors |
| Pixel Pitch | 0.18159 mm |
| Refresh Rate | 24-75Hz (60Hz recommended) |
| Dimensions (W x H x D) | 31.7" x 24.1" x 14.7" (809.34 mm x 612.35 mm x 374.16 mm) |

| | |
|---------------------------------|---|
| Dimensions without Stand | 31.7" x 14.4" x 4.1" (809.34 mm x 365.83 mm x 104.6mm) |
| Panel Depth | 4.1" (104.6 mm) |
| Display Weight | 22.1 lb/10 kg (15.4 lb/ 7kg without stand) |
| Shipping weight | 27.6 lb (12.5 kg) |
| Video Inputs | USB Type C (DisplayPort Alt Mode), DisplayPort, HDMI® |
| HDCP | Yes |
| Audio Output | Integrated 2W/channel stereo speakers, headphone jack |
| External Connections | USB Type C, HDMI 19-pin, DisplayPort 20-pin, 3.5mm headphone out, USB 3.2 Gen 1 (Type A) x 3, RJ45. |
| USB | USB-C x 1 (Upstream) (5Gbps), USB3.2 Gen1 x 3 (Downstream) |
| USB C Power Delivery | USB C (Up to 65W) (5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A) |
| RJ45 | Ethernet LAN (10M/100M/1000M) |
| Compatibility | PC and Mac® (adapter may be required for Mac) |
| Power Supply | Internal |
| Power Consumption (max) | 35W typical (<0.5W standby) |
| Power Requirements | AC 100/240 VAC |
| Operating Temperature | 0° to +40°C (32° to 104°F) |
| Humidity | 20 - 90% RH (non-condensing) |
| Mount | Built-in 100 mm VESA, back |
| Product Approvals | cTUVus, CE , FCC-B, RoHS |
| Recommended Usage | Up to 16 hours per day |
| Service and Support | 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. |
| Options / Features | IPS panel, Wide color consistent viewing angle, Discreet branding, Height adjustment: 5.1" (130cmm), Swivel range 360° (180° left, 180° right), Pivot 90°, Anti-glare coating ,Multi-language display, On screen display (OSD), Kensington® Security Slot |

| | |
|----------------------|---|
| Blue Light Reduction | Yes |
| Flicker Free | Yes |
| In the Box | PZN3210U 32" LCD Monitor, Power Cord, HDMI & DP Cable, USB Type-C Cable, User's Guide |
| UPC | 8 10689 00924 5 |
| HDMI® | Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. |

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 9/27/2024

© Copyright 2024 Planar Systems, Inc. All rights reserved