

Planar Helium PCT2495

24" Touch Screen Monitor

The Planar[®] Helium[™] PCT2495 is a 24" Full HD resolution (1920x1080) 10-point touch screen LCD monitor with Planar[®] ERO-LCD[™] protective glass, integrated webcam, speakers, USB hub and adjustable desk stand.



| SPECIFICATION | DETAIL |
|---------------------------------|---|
| Product Name | PCT2495 |
| Planar Part Number | 998-3328-00 |
| Viewable Size | 23.8" diagonal (20.75" horizontal x 11.67" vertical) |
| Touchscreen Type | Optically Bonded Multi-Touch Projected Capacitive (up to 10 touch points) |
| Number of Touch Points | 10 |
| Touchscreen Interface | USB |
| Contrast Ratio (typ) | 1000:1 |
| Viewing Angle (typ) | 178° H,V |
| Response Time (typ) | 14 ms, 5ms (G to G) |
| Brightness (w/touchscreen) | 360 cd/m² |
| Brightness (w/o touchscreen) | 400 cd/m² |
| Display Type | IPS Edge-Lit LED LCD |
| Display Resolution | 1920 x 1080, full HD |

| Aspect Ratio | 16:9 |
|-------------------------------|---|
| Tilt Range | +15° to +65° and flat |
| Palette | 16.7 million colors |
| Pixel Pitch | 0.2745 mm |
| Refresh Rate | 50 to 75 Hz (60 Hz recommended) |
| Panel Depth | 1.7" (43.6 mm) |
| Dimensions (W x H x D) | 22.3" x 13.3" x 1.7" ; (556.1 mm x 337.3 mm x 43.6 mm) |
| Dimensions without Stand | 22.3" x 13.3" x 1.7" ; (556.1 mm x 337.3 mm x 43.6 mm) |
| Display Weight | 9.7 lb (4.4 kg) |
| Display Weight (w/o stand) | Not applicable. Integrated stand folds into the monitor. |
| Shipping weight | 12.6 lb (5.7 kg) |
| Video Inputs | HDMI®, DisplayPort (w/HDCP) |
| HDCP | Yes |
| Audio Output | 2 speakers, 1W/ch, headphone out |
| Compatibility | Windows $\$ 7, 8, 10, 11 - HID Compliant, Chrome OS, Android & Linux (Kernel above version 3.8)- no drivers needed for basic touchscreen operation |
| External Connections | HDMI 19-pin, DisplayPort 20-pin, 3.5mm headphone out, USB (A to B), USB 3.0 A type x 2, AC power-in |
| Power Supply | Internal Power Supply (AC power) |
| Power Requirements | 100-240 VAC, 50/60 Hz |
| Power Consumption (max) | 35W typical (<1.0W standby, off) |
| Operating Temperature | 0 to 40°C |
| Humidity | 10 - 90% RH (non-condensing) |
| Mount | Built-in 100 mm VESA, back |
| Recommended Usage | Up to 16 hours per day |
| Service and Support | 3-Year Customer First [™] Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for |

| | replacement procedures outside the US. |
|----------------------|---|
| Options / Features | Integrated HD (720p) webcam with microphone; MPP2.0 Active Pen Compatible, built-in USB Hub -USB 3.0 - x 2, Kensington® Security Slot |
| Blue Light Reduction | Yes |
| Product Approvals | UL/c-UL, FCC-Class B, CE, RoHS |
| CI-Black-PN | 998-3328-00 |
| In the Box | PCT2495 24 inch Wide Multi-Touch Monitor, Power Cord, HDMI Cable, DP Cable, USB Cable (A to B), User's Guide, Cleaning Cloth, Cable Wrap |
| UPC | 8 10069 81077 5 |

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 9/27/2024

© Copyright 2024 Planar Systems, Inc. All rights reserved