



# Planar TWA1.2

TWA1.2\_1

The Planar® TWA1.2 is a fine pitch LED video wall display with a 1.2 millimeter pitch. The Planar TWA1.2 delivers benefits unique to its “flat panel” design including enhanced image quality, a 16:9 form factor optimized for the most popular high resolutions, ease of installation and service, and outstanding flatness and uniformity. With a power-efficient design, the Planar TWA1.2 significantly reduces power utilization while delivering additional image optimization features.



SPECIFICATION	DETAIL
Product Name	TWA1.2
Pixel Pitch	1.25mm
LED Type	Commercial grade 3-in-1 Black SMD
Cabinet Resolution	960 x 540
LEDs per Cabinet	518,400
Pixel Density	640,000 / sq m   59,450 / sq ft
Cabinet Size (W x H x D)	1200 x 675 x 100mm   47.24 x 26.57 x 3.94in
Cabinet Diagonal	1377mm   54.21in
Cabinet Area	0.81 sq m   8.718 sq ft
Modules/Cabinet (W x H)	5 x 4
Module Resolution	192 x 135
LEDs per Module	25,920
Module Size	240 x 168.75mm   9.44 x 6.64in
Power Consumption, Maximum (watts)	440 / Cabinet   543 / sq m

<b>Power Consumption, Typical (watts)</b>	132 / Cabinet   162 / sq m
<b>Line Voltage</b>	100-240V AC, 50/60Hz autoranging
<b>Cabinet Weight (per display)</b>	30 kg   66.1 lb
<b>Cabinet Weight (per m<sup>2</sup>)</b>	37 kg / sq m   81.6 lbs / sq m
<b>Brightness Max (cd / sq m)</b>	800
<b>Contrast Ratio</b>	> 6,000:1
<b>Brightness Uniformity</b>	>97%
<b>Color Uniformity</b>	>97%
<b>Color Gamut</b>	100% NTSC
<b>LED Refresh Rate</b>	3,000 Hz
<b>Color Temperature, Adjustable (k)</b>	3,200 - 9,300
<b>Viewing Angle, Horizontal</b>	160°
<b>Viewing Angle, Vertical</b>	140°
<b>LED Surround</b>	Black Solder Mask
<b>Video Inputs</b>	2x HDMI in, 2x HDMI out; HDCP Compliant
<b>Video Input Resolution Maximum</b>	1920 x 1080 @ 60Hz
<b>Frame Rate</b>	50, 60Hz
<b>Control Input Type</b>	RS232 or Ethernet
<b>Gray Scale Processing</b>	16-bit
<b>Service Access</b>	Rear
<b>LED Lifetime (Half Brightness)</b>	100,000 hrs
<b>Environment</b>	Indoor
<b>Power Supply</b>	Single. Dual optional
<b>Protection</b>	IP30, Planar® ERO-LED™ Technology (optional)
<b>Acoustic Noise</b>	Fanless Operation
<b>Operating Temperature/Humidity (degrees F/C) 10-80% relative humidity, non-condensing</b>	-10° to 40° C   14° to 104° F
<b>Storage Temperature/Humidity (degrees F/C) 10-85% relative</b>	-20° to 60° C   -4° to 140° F

humidity, non-condensing	
Regulatory Compliance	NRTL UL 60950-1, FCC Class A, CE EN60950-1, EN 55032 Class A and EN 55024, WEEE, CISPR 32/2015
Warranty	3 years; 24-hour customer service
HDMI®	Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 9/27/2024*

*© Copyright 2024 Planar Systems, Inc. All rights reserved*